

UNIVERSAL NON-PENETRATING ROOF MOUNT



SPECIFICATIONS

- Sizes available – Base 36" X 36"
- 1.66" OD Bent Mast/Foot (not included)
- 2.0" OD Bent Mast/Foot (not included)
- 2.375" OD Bent Mast /Foot (not included)
- Weight – 25, 29 and 31 lbs respectively with pad.
- Material – 500 Hour Salt Spray Steel (various coatings available depending on corrosion requirements), Powder Coated.
- Mounting – Non-Penetrating requiring ballast (concrete cinder blocks).
- Options – NPRM Pad for roof protection – recommended with all installations.
- Optional Hardware – Grounding lugs
- Packaging – 80 pallet load or single pack.
- Mounting surfaces included: roof.
- Other Mounts Available – Universal, Roof/Wall and Ground Pole Mounts.

DEDICATED NON-PENETRATING ROOF MOUNT



SPECIFICATIONS

- Sizes available – Base 36" X 36"
- 1.66" OD Mast
- 2.0" OD Mast
- 2.375" OD Mast
- Weight – 25, 29 and 31 lbs respectively with pad.
- Material – 500 Hour Salt Spray Steel (various coatings available depending on corrosion requirements), Powder Coated.
- Mounting – Non-Penetrating requiring ballast (concrete cinder blocks).
- Options – NPRM Pad for roof protection – recommended with all installations.
- Optional Hardware – Grounding lugs
- Packaging – 80 pallet load or single pack.
- Mounting surfaces included: roof.
- Other Mounts Available – Universal, Roof/Wall and Ground Pole Mounts.